



LITHIUM 24-120 BATTERY MANUAL



LEGAL GUARANTEES

In accordance with Law 1480 of 2011 Consumer Statute and Decree 735 of 2013 Legal Guarantee:

- To request a guarantee, the customer is obliged to report the damage to the product, make it available to the company at the guarantee service point at AV CL 80 69-70 Unit 1C, and indicate the invoice number to determine your purchase date.
- The delivery of the repaired product will be delivered to the customer at the warranty service point, unless the customer requests to send it to a different destination, in which case the customer must assume the cost of freight.
- In any case, when a product repair guarantee is denied or approved, the respective written report must be issued supporting the evidence that justifies the decision.
- In no case will Tb Plus Energy proceed with the replacement of the product given under warranty since, if the repair does not proceed, a credit note will be issued which covers the acquisition of another new product or service or the return of the money paid.
- If the failure repeats once the product has been repaired, only the credit note applies which covers the acquisition of another new product or service or the return of the money paid.
- When the customer opts for a refund of the money, it will be for the amount of the sale price. For this purpose, they must send a communication signed by the legal representative, which indicates the bank details to make the return, the which will be effective within fifteen (15) business days after receipt of the return request.
- The repair of the product will be carried out within 30 business days following the claim, which is carried out by filling out the GP-F-018 Warranty Form, which is completed in the PQRF Guarantees tab on the WEB page www.tbplusenergy.com or at the following link:

https://forms.office.com/Pages/ResponsePage.aspx?id=K987JK0Nuke_1n30RF9URwiKWAfZovhDrWEVYGmhK95UOVZYUFBWMUpaQVZBM0hIS0RKUjdLSkdIWS4u
- Once the guarantee form has been completed, the client has 15 days to make it available at the guarantee service point.
- The product manuals in which proper use, installation instructions and periods covered by the warranty are reported are found in the PQRF Product Manuals tab on the website www.tbplusenergy.com.

TECHNICAL SPECIFICATIONS

Product description

Lithium iron phosphate (LiFeP04) batteries are designed to outperform traditional lead-acid batteries on the road, in the water or off the grid. Offering more usable power in a lightweight, maintenance-free package that's safe, reliable and worry-free.

Main properties


- High energy density.
- High resistance to high temperatures and humidity.
- High efficiency between charging and discharging, with very little energy loss.
- Good charging efficiency at high temperatures.
- High charging currents that allow charging times to be shortened.
- Superior useful life.
- Electronically regulated temperature management by BMS.
- High energy retention.
- Integrated electronics.
- High security: built-in protection functions.
- Simple installation.
- Greater care for the environment and less pollution.

TECHNICAL VARIABLES


Dimensions and Features		
	TB 24-120AH	
Capacity nominal	120AH	
Weight	23kg	
Length (mm)	522	
Width (mm)	240	
High without Terminal (mm)	222	
Capacity (25°C) - 10 hour rate	(12A)	120ah
Specification		
Voltage	24V	
Internal resistance	<30mΩ	
Affected capacity by temperature	40 °C	101 %
	25 °C	100 %
	0 °C	93 %
	-20 °C	65 %
Residual capacity	Cap. after 3 months of storage	87 %
	Cap. after 6 months of storage	74 %
	Cap. after 12 months of storage	50 %
Position (Constant Voltage)	Cycle (25° C)	Initial charging current less than 30A Voltage 28.6 - 29.2V
	Float (25° C)	Charging voltage 27.2 ~ 27.6v
Current discharge (25°C)	4A (0.2seconds); 60A (5 seconds)	

GRAPHICS

Download Features




Charging voltage characteristics




GRAPHICS

Life cycle in relation to depth of discharge



Residual capacity



WARRANTY CONDITIONS

Tb Plus Energy guarantees that each product is free of defects in materials and manufacturing, and offers a guarantee for a period of 36 months from the purchase of the product.


RECOMMENDATIONS


- Follow loading and unloading recommendations.
- Charge to 100% on the first charge.
- Store in a safe place. Free of light, water and dust.
- Install under certified professional recommendation.
- Do not expose to nearby heat sources.
- Do not connect equipment with a power higher than that for which the battery or system has been sized.
- Once a year check the battery charge level.
- Keep the battery free of objects and obstacles.
- Do not manipulate its edges with your hands.
- Do not leave them within the reach of children.
- It is not recommended to install series and parallel simultaneously.
- It is recommended not to make more than one series (no more than two batteries), using 24V 120Ah LIFEP04 batteries, as it may affect their operation due to the design of the internal BMS.
- More than 4 batteries should not be used in parallel connection since their terminal blocks, wiring and BMS can overheat, causing a short circuit, due to the high operating current.


*Other battery capacities can be developed and supplied upon request.


Tb Plus [®]


 www.tbplusenergy.com

 (+57) 316 6159244

 Av. Calle 80 No 69-70
Bodega 35.
Bogotá D.C. - Colombia

 (+1) 814 3008183

 759 SW Federal HWY
Suite 304
Stuart - Florida - US

 (+86) 13818126326

 China - Shanghai;
Cod. Postal 201308
Ed 1y2 N° 333;
Haiyang 1st Road